



United States Patent [19]
Pericic et al.

[11] **Patent Number:** **5,923,467**
[45] **Date of Patent:** **Jul. 13, 1999**

[54] **BINOCULAR BENT-AXIS LOUPES**
[75] **Inventors:** Ljubomir Pericic, Alphington; Gerard W. Crook, Kew; Hugh R Taylor, Balwyn, all of Australia

[73] **Assignee:** The University of Melbourne, Victoria, Australia

[21] **Appl. No.:** 08/244,554

[22] **PCT Filed:** Nov. 26, 1992

[86] **PCT No.:** PCT/AU92/00634

§ 371 Date: Sep. 1, 1994

§ 102(c) Date: Sep. 1, 1994

[87] **PCT Pub. No.:** WO93/11454

PCT Pub. Date: Jun. 10, 1993

[30] **Foreign Application Priority Data**

Nov. 28, 1991 [AU] Australia PK9740

[51] **Int. Cl.** ⁶ G02B 27/02; G02B 7/02; G02B 23/02; G02C 1/00

[52] **U.S. Cl.** 359/411; 359/412; 359/385; 359/368; 359/409; 359/482; 351/158; 351/159

[58] **Field of Search** 359/411, 412, 359/431, 413, 414, 375, 377, 385, 368, 409, 480, 481, 482, 471, 473, 475, 476, 477, 478, 479, 647, 661; 351/158, 159

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,049,972 8/1962 Malinowski 359/431
3,847,470 11/1974 Dederer et al. 351/6
3,909,106 9/1975 Buhler 359/377
4,152,054 5/1979 Leiter 354/23
4,251,128 2/1981 Feinbloom 359/385
4,264,122 4/1981 Schmidt et al. 359/412

4,302,087 11/1981 Reisheimer et al. 354/79
4,303,340 12/1981 Hoffman 356/372
4,652,094 3/1987 Kitajima 359/375
4,704,000 11/1987 Pekar et al. 359/431
4,795,235 1/1989 Spitzberg 351/158
4,991,947 2/1991 Sander et al. 359/375
5,020,891 6/1991 Lichtman et al. 359/431
5,191,470 3/1993 Wickholm et al. 359/375
5,204,489 4/1993 Pellarin et al. 359/431

FOREIGN PATENT DOCUMENTS

680766 9/1939 Germany 359/431
447299 8/1950 Italy 359/431
187311 10/1984 Japan 359/431
322460 12/1929 United Kingdom 359/423

OTHER PUBLICATIONS


Harris, Optical Transducer, Oct., 1960, pp. 55-56.

Primary Examiner—Cassandra Spyrou
Assistant Examiner—Mohammad Y. Sikder
Attorney, Agent, or Firm—Foley & Lardner

[57] ABSTRACT

Optical loupes comprise a frame supporting two optical devices, each of which has an ocular and an objective. The frame has side arms or stems and a bridge for enabling the frame to be worn like a pair of spectacles, whereby the optical devices are located immediately in front of the eyes of the viewer. The ocular and the objective each have an optical axis. The optical axis of the ocular and the optical axis of the objective intersect at an angle of about 135°, and a Schmidt prism redirects light from the objective to the ocular in each case. A light source is provided on the frame between the optical devices and provides a gradually diverging light beam to illuminate an object being reviewed. The optical axes of the respective objectives converge at the object being reviewed. The loupes allow the user to observe at a level below his or her normal line of sight while maintaining the head in an upright position.

15 Claims, 3 Drawing Sheets



00905662, 071301